

SO C70600 Slip On Pipe Flange Fittings ASTM B151 Copper Nickel 1/2" To 48"

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Kasugai
- Certification: ISO PED AD2000
- Model Number: C70600 ANSI B16.5/B16.47 SO
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: Seaworthy Packing
- Delivery Time: 30 - 60 working days
- Payment Terms: L/C, T/T
- Supply Ability: 200 ton per month



Product Specification

- Product Name: ASTM B151 C70600 ANSI B16.5/B16.47 Copper Nickel Slip-On (SO) Flanges
- Size Range: 1/2" To 48"
- Pressure Class: Class 150, 300, 400, 600, 900, 1500, 2500
- Thickness: Sch10S To Sch160
- Face Type: Slip-on (SO)
- Standards: ASTM B151, ASME/ANSI B16.5/B16.47, JIS B2220
- Highlight: **ASTM Slip On Pipe Flange, ASTM B151 Pipe Flange Fittings, ASTM B151 Slip On Pipe Flange**

for more products please visit us on flangespipefittings.com

Product Description

ASTM B151 C70600 ANSI B16.5/B16.47 Copper Nickel Slip-On (SO) Flanges

Product Information

Product Name	ASTM B151 C70600 ANSI B16.5/B16.47 Copper Nickel Slip-On (SO) Flanges
Size Range	1/2" to 48"
Pressure Class	150, 300, 400, 600, 900, 1500, 2500,
Thickness	Sch10S to Sch160
Standards	ASME/ANSI B16.5/B16.47, JIS B2220
Type	Slip-On (SO)
Dimensions	ASME/ANSI B16.5/B16.47, Custom Drawings
Origin	China

Standards & Materials: ASTM B151

Chemical Composition of ASTM B151 (%)

UNS	C	Ni	Pb	Fe	Mn	Zn	P	S	C
C70600	Remainder	9.0-11.0	0.05	1.0-1.8	1.0	1.0			
C71500	Remainder	29.0-33.0	0.05	0.40-1.0	1.0	1.0			

Mechanical Properties of ASTM B151 C70600

Temper Code	Dia. or Distance Between Parallel Surfaces (mm)		Tensile Strength, min (MPa)	Yield Strength at 0.5% Extension Under Load, min (MPa)	Elongation in 4xDia or Thickness of Specimen, min (%)
O60, M30	Round, Hex and Octagonal rods and square bars	All sizes	260	105	30
H04	Round, Hex and Octagonal rods and square bars	Up to 9.5, incl	415	260	10
		Over 9.5 to 25, incl	345	205	15
		Over 25 to 80, incl	275	105	30
		Over 80 to 125, incl	260	105	20
O60	Rectangular bars and shapes	All sizes	260	105	30
H04	Rectangular bars	Up to 9.5, incl	380	205	10
		Over 9.5 to 12, incl	345	195	12
		Over 12 to 80, incl	275	115	20
H04	Shapes	All sizes	(As agreed upon between the manufacturer or supplier and the purchaser)		

Flange Type: Slip On (SO)

Slip on flange also simplified as SO flange. SO flanges slip over pipes and are designed to fit slightly bigger on the inside than the pipe. They connect to the pipe through a fillet weld at the flange top and bottom. It is used to insert the pipe into the inner hole of flange, as the flange inner diameter is little bigger than the pipe's outer diameter, pipe and flange could be connected by lap welding at the top and bottom of the flange.

The slip on flange is shorter in length than a weld neck flange, and is used in areas where short tie-ins are necessary or space limitations necessitate its use. Generally, the life span of a slip-on flange connection is about one-third that of the weld neck flange. Despite of additional welding involved during installation, its lower initial cost makes the SO flange preferred over WN flanges by many users. It is generally used in non-corrosive, non-critical, moderate pressure services. Slip on flanges of Class 150 and Class 300 are most commonly seen in utility engineering.




Illustration of welding a pipe to a slip-on flange conforming to ASME B16.5: two fillet welds shall be furnished.



A sample picture of a slip on flange



Kasugai Shanghai Co., Ltd.

+8109093329324

zhangying@kasugai-group.co.jp

flangespipefittings.com

Rm.8415, Bldg. A8, No. 808 Hongqiao Road, Xuhui District, Shanghai 200030, China